



TROYLUBE
Motor Oils and Lubricants

TROYLUBE **ATF DEXRON III**

Automatic Transmission Fluid

TROYLUBE ATF DEXRON III is a premium automatic transmission and power steering fluid that can be used in many vehicles, especially European and North American vehicle manufacturers. It has been formulated with state-of-the-art additive packages to meet GM Dexron IIIH and Ford Mercon performance levels and provides a smooth transmission operation even in wide and difficult operating conditions.

Properties

- Provides trouble-free performance by providing easy pumping and circulation during the first start even at low temperatures.
- It protects the automatic transmission and extends its life thanks to the rust and corrosion preventive additive packages it contains.
- Provides smooth and comfortable gear shifting even under hardworking conditions.
- Provides perfect lubrication by forming a very good film layer, prevents abrasions in gear and bearings.
- It prevents foam formation.
- Prevents leaks as it is compatible with sealing elements.

Approvals and Specifications

- GM DEXRON® IIIH
- Ford MERCON®
- MAN 339 Type V-1
- Caterpillar TO-2
- VOITH G 607
- VOITH H55.6336.41
- ZF TE-ML 17C
- ZF TE-ML 14B
- Allison C-4
- MAN 339 Type Z-2
- MB-Approval 236.9
- MB-Approval 236.6
- MAN 339 Type Z-2
- Volvo 97341, Volvo 97340
- ZF TE-ML 16L
- ZF TE-ML 09/11/14



TROYLUBE

Motor Oils and Lubricants

Technical Specifications

Test	Method	Typical Properties
Density (15 °C), g/cm ³	ASTM D1298	0,843 – 0,878
Kinematic Viscosity (100°C), mm ² /s	ASTM D445	6,3 - 8,8
Viscosity Index	ASTM D2270	Min. 160
Flash Point, °C	ASTM D92	Min. 200
Pour Point, °C	ASTM D97	Max. -40

